



**PYRAMEX**  
Perform At Your Peak

**PMXSLIM®** ANSI CE AUS



ADJUSTABLE  
NOSEPIECE



CO-INJECTED  
TEMPLES

Slim fit for smaller facial features

Soft, adjustable nosepiece

Co-injected temple design includes soft rubber tips for a non-slip fit

Part No.	Black Temples
ESB7110S ●●	Clear
ESB7110ST ●●●	AF Clear H2X
ESB7120S ●●	Gray
ESB7120ST ●●●	AF Gray H2X
ESB7130S ●●	Amber
ESB7138S ●●●	Sandstone Bronze
ESB7180S ●●●	I/O Mirror



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) or Australian [AS/NZS 1337] (●) standards. For specific lens options visit our website or contact your sales representative.

## PMXSLIM®

### General Specifications

Weight: 25 gm  
 PD: 68 mm  
 Bridge: 14.5 mm  
 Lens base: 10 curve  
 Lens size diagonal: 137.7 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 170 mm  
 Overall width (hinge - hinge): 129 mm  
 Closest point between temple tips: 86 mm  
 Closest point between lens: 9 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Side shields: polycarbonate  
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
ESB7110S	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB7110ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB7120S	5 -2.5 P 1 F CE	CE P EN166 F
ESB7120ST	5 -2.5 P 1 F N CE	CE P EN166 F
ESB7130S	2 - 1.2 P 1 F CE	CE P EN166 F
ESB7138S	5 -2.5 P 1 F CE	CE P EN166 F
ESB7180S	5 -1.7 P 1 F CE	CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Color perception

C: Unimpaired color perception

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 N: Filter with anti-fog  
 CE: Europe standard

### Frame Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com