



EN ISO 20344:2011



CRYSTAL  
**ANCONA**  
86202-00

S2 \*CI SRC

**Size:** 35-39 40-48  
**Weight:** 510 gr.

**Fit:** 11

**Working Environment:**  
Food and Chemical industry,  
Ho.Re.Ca.



## FEATURES

### UPPER

MicroFiber XPRO 1,8-2,0 mm

### LINING

Bacteriostatic Teklife 3D  
Double non-slip layer of  
microfibre, resistant up to 200,000  
cycles. Makes the footwear more  
comfortable, blocking the foot  
during use.

### INSOLE

Flyfit

### TOE CAP

Fiber cap SXT

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY SRC

Double density PU outsole with  
tread designed mainly for indoor  
use. Self-cleaning design and  
highly non-slip grip. SRC Antislip  
standard.

## TECHNOLOGIES

### Removable Insole



The upper layer in contact with the  
foot is made of a highly resistant  
netting to ensure exceptional  
absorption of dampness. A self-  
forming antibacterial foam layer  
ensures comfort and correct support  
of the foot.



### Protection elements

**fibercap sxt**

Composite toecap, reinforced with  
fiberglass. Structure with a variable  
thickness for better performances



### Lateral stability

**dynamic HC control**  
technology

Ergonomic rigid internal structure. It  
houses the heel into the right seat,  
adjusting the foot support and control  
of the ankle sideways movements. It  
keeps the foot tight to the shoe,  
allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic  
material. It stabilizes the heel bone,  
the instep and tarsal joints, without  
altering energy absorption. A support  
for the natural movement of the foot;  
it provides comfort and greater  
stability.



### Electrical features



Wire Electricity Discharge


Strip with 4 filaments of carbon fiber,  
ensuring proven anti-static properties  
of the footwear over time.



### Other

**DUAL MICRO**  
**DNV WICBO**

Double non-slip layer of microfibre,  
resistant up to 200,000 cycles. Makes  
the footwear more comfortable,  
blocking the foot during use.



## SRC (SRA+SRB)



SOLE 86  
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.40 0.32
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.24

EN ISO 20344:2011